

## STAIN BLOCK PRIMER

**Dulux Trade** Stain Block Primer is a water-based primer suitable for use on interior walls and ceilings. It is formulated to prevent the migration of stains through the finished paint film and also to seal and bind dry, friable and powdery interior surfaces such as plaster, brick and distemper. It is the effective treatment for stains caused by: water-based and solvent-based inks, crayon, biro, coffee, grease, scuff marks, water and nicotine.

### KEY BENEFITS

- Interior Walls & Ceilings
- For Stains Including Smoke Damage, Nicotine & Inks
- Seals Powdery Surfaces, Limewash & Distemper

### PRODUCT INFORMATION

#### Typical Use

Suitable for use on normal interior wall and ceiling surfaces.

#### Pack Size

1L, 2.5L and 5L.

#### Colour Range

White only.

#### Composition (nominal)

**Pigment:** Titanium dioxide, zinc oxide & inert extenders.

**Binder:** Water-based emulsion.

**Solvent:** Water.

#### Volume Solids

43% (nominal).

### SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as efflorescence, dirt, grease or wax.

Where necessary, surfaces should be rubbed down using a suitable abrasive paper and then dusted off (refer to your COSHH Assessment). Do not abrade **Dulux Trade** Stain Block Primer before recoating.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

### SYSTEMS INFORMATION

**STIR THOROUGHLY BEFORE USE.** After suitable surface application, apply 1 coat of **Dulux Trade** Stain Block Primer to all bare or stained surfaces and allow to dry. Two coats will be necessary for difficult stains.

When blocking stains caused by water or damp, make sure the original cause of the problem has been rectified. When **Dulux Trade** Stain Block Primer is applied initially, it will draw the stain into itself and then seal it – this is not a defect.

Finish with an appropriate **Dulux Trade** paint system.

### APPLICATION METHOD

Brush or short pile roller only. Do not spray.

As with all water based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

#### Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 14m<sup>2</sup> per litre.

#### Thinning

This product does not require thinning.

#### Spray Recommendations

This product is not suitable for spraying.

#### Drying Times

*Single coat at standard thickness:*

**Touch Dry:** Dependent on temperature and humidity.

**Recoat:** 6-8 hours. *Note:* on very porous surfaces, a longer drying time may be required.

## STAIN BLOCK PRIMER

### Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at [duluxtrade.co.uk/pp](http://duluxtrade.co.uk/pp).

### Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

### VOC

EU limit value for this product (cat.: A/h): 30g/l (2010). This product contains max. 25g/l VOC. VOC content: Low (0.30-7.99%).

## FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

***Always read full Health, Safety & Environmental Information on can before use.***

Safety datasheet (SDS 307) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting [duluxtrade.co.uk](http://duluxtrade.co.uk).

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.